

LUNA 200 P

Mammuth
Din belysningspartner

LUNA 200P is a powerful linear light fixture, provided with optics for an even and glare-free light experience.

Developed with the game in focus

LUNA 200 P is developed to give an even and glare-free light on the padel court. The optimal installation height for the fixture is 8-12 meters above ground. The optics in the light fixture ensures that the light is evenly distributed over the court, which results in neither dark spots nor glares.

Complete installation kit

LUNA 200 P is normally installed using track lines, which is hanging from the ceiling. Accessories such as mounting rails and suspension hanging kit/clutch wire can of course be provided by Mammuth.

For an effective installation, we are also offering the fixtures preinstalled with the markets most common, easily installed, connection system, preconnected with the necessary cables. This is to ease either a transition, new-installation, or if you want to upgrade to a ceiling mounted light fixture.



Color temperature (CCT) for all your needs

LUNA 200 P standard CCT is 4000K – but is also available in a range between 3000K up to 5700K.

Excellent for light controlling

LUNA is excellent for light controlling, since it lights up instantly, and without any warm-up time. In other words, you can start the game right away. This also makes LUNA compatible with booking-systems, such as Playtomic or MATCHi.

Big savings

By replacing traditional light fixtures with modern LED fixtures like LUNA 200 P, you will be able to lower your operating and maintenance costs with a considerable amount - often by 80% or more.

Mammuth is happy to help you with light and energy calculations. Besides this, we can also provide financial solutions where you will receive the cost savings from the first day.

Mammuth AB
Företagshusvägen 5
S-244 93 KÄVLINGE
SWEDEN

www.mammuth.se
+46-46-2769505
info@mammuth.se

LUNA 200 P

Technical data

Model:	LUNA 200 P II
Input, power	200 W
Luminous:	30.000 lm
Lumen efficacy:	150 lm / W
CRI:	> 80 Ra
MacAdam:	3 SDCM
CCT:	4000 K (also available in 3000 K, 5000 K, 5700 K)
Light control:	1-10 V or Dali as an option
Material:	aluminum / polycarbonate
IP-rating:	IP 65
Dimension:	1154 * 155 * 144 mm
Lifespan:	100.000 hours L90 B10 (Ta 25) (-30°C to +50°C)
Cycles:	> 100.000

Mammuth stands for quality, availability, and service. We are flexible in our mindset and advocate an open and honest dialogue. This is what we aim to deliver, in both our products, and our collaboration with you.

We are living in a very exciting and interesting time, with great advancements within technology that contributes to easier user experiences. This is also true within the LED industry, where the relatively new and favorable LED-technique gives us many new advantages.

With our products, we are going to help you to solve your lighting needs, and at the same time lower your energy costs, improve your working conditions, and together, contribute to improving the global environment.

We want to help you realize your thoughts, ideas, and needs, and we promise you first class service! Good lighting is not noticed, but bad lighting takes unnecessary energy from your core business.